"Mordan Everpoint"

Quality Pencils.

To operate this pencil propel the lead as required.

When a lead is exhausted :

d hadle the

beriuper.

Wind back the propeller "A" as far as possible, Withdraw the outer sheath "B,"

Take a new lead from the reserve end "C" and drop it into carrier "D,"

ogerate

When the less particle of lead have been and been a set of the sheath B, carrier A as far as possible. Withdraw the outer sheath **.a**su rof berupar as head as required for the sheath **.a**su rof berupar as the sheath as the sheath **.a**su rof berupar as the sheath as the sheath **.a**su rof berupar as the sheath as the sheath **.a**su rof berupar as the sheath as the sheath **.a**su rof berupar as the sheath as the sheath **.a**su rof berupar as the sheath **.a**su rof

Do not wind back the propellor or remove the sheath untils a new lead is required, this required, the sheath untils a new lead is

N.B.—This Ever-pointed Pencil is the only type that ensures an absolutely Replace the sheaf B and pro thing point and bro use.

All pencils have a supply of leads in the Reserve Chamber. ton of

All pencils have a supply of leads in the Reserve Chamber. REFILL LEADS: 90 rod rod . PC BLAEL LEADS.

Supplied in Hard, Medium, and Soft grades, also Indelible.

Supplied in Hard, Medium aud Soft grades, also Indefible.

ICAUTION.-In S. MORDAN & CO.'S EVER-POINTED PENCILS, S. MORDAN & CO.'S LEAD REFILLS only should be used. More damage results from ill-fitting leads than from all other causes combined.

Can be obtained from any Jeweller, Stationer or Store throughout the World. Can be obtained from any Jeweller, Stationer or Store throughout the World.

S. MORDAN & CO., Ltd., Inventors and Patentees, 41 Gity Road, London, E.C. 1.



Quality Pencils.

PROPELLING, REPELLING, AND EJECTING, WITH ERASER.

To operate this pencil propel the lead as required.

MORDAN EVERPOINT

MORDAN

OWhen a lead is exhausted:
Owner in the second is exhausted:

Image: Second is exhausted:
Image: Second is exhausted:

Image: Second i

omini i goub The lead can be retired at will by reversing the action.

- When the last particle of lead has been ejected by the rod E, wind back the carrier A as far as possible,
- Withdraw the outer sheath B," and bar required as required for B," with the lead as required for the bar of the sheat the shea

coll propel the lead as required.

Take a new lead from the reserve end C, by removing the cap D and the rubber holder F (where fitted),

Drop the lead into the conductor G and press well home; og rov H zidT _ H M

Replace the sheaf B and propel the lead as required for use.

Do not remove the sheath until a new lead is required. along IIA

All pencils have a supply of leads in the Reserve Chamber.

REFILL LEADS: 9d. per box of 15 Leads.

Supplied in Hard, Medium and Soft grades, also Indelible.

CAUTION.—in S. MORDAN & Co.'s EVER-POINTED PENCILS, S. MORDAN & Co.'s LEAD REFILLS only should be used. More damage results from ill-fitting leads than from all for other causes combined.

REFILL RUBBERS: 1/- per box of 12 Rubbers.

Can be obtained from any Jeweller, Stationer or Store throughout the World.

S. MORDAN & CO., Ltd., Inventors and Patentees, 41, City Road, London, E.C. 1.