

PRECISION PENCIL LOADING

Hold barrel and turn cap clockwise until all lead is expelled and metal rod appears at point. Then turn back completely . . . insert lead . . . and press against a hard surface to seat lead in clutch.



CONVERTER FILL SYSTEM Unscrew barrel and insert converter. Immerse point of pen completely in Skrip® writing fluid. Squeeze the converter spring lever two or three times. Wait five seconds before removing point from fluid. Replace barrel. (Adapt to cartridge use any time by removing inner apparatus.)



SKRIP® CARTRIDGE FILL Grip section near point. Unscrew barrel, insert cartridge (either end first) into barrel. Screw on point section to engage. On first fill of new pen, squeeze cartridge gently to ease fluid into point. Replace barrel. Do not attempt to push cartridge directly onto the pierce tube.



DESK SET ASSEMBLY

Push socket into base until it snaps firmly in place . . . and still swivels freely. Remove from base by pulling socket straight up.

DESK SET REPAIR: Send only portion of desk set (pen, socket or base) requiring attention. In case of chipped or broken base, you will receive a written quote of base exchange prices.

ATTACHING A "PUT-ABLE" PEN

Remove paper cover from bottom of self-adhesive base. Then "put" it almost anywhere, on almost anything – metal, glass, plastic, wood. Create your own "original" desk set.

A-677

SHEAFFER, WORLD-WIDE, A textron COMPANY

SHEAFFER. the proud craftsmen Printed in Great Britain

Guarantee

This Sheaffer writing instrument is guaranteed against mechanical defects. Upon return of the instrument to the factory, Sheaffer will repair mechanical defects free of charge or replace the instrument with merchandise of equivalent value.

SHEAFFER, WORLD-WIDE, A textron COMPANY . FORT MADISON, IOWA 52627

In Canada: Goderich, Ontario. In Australia: Melbourne. In Great Britain: Hemel Hempstead.

